

V6CO.

「CARE HEALTH CARE LIFE」
Dr.@home Series

THE LOVE FOR MOTHERS



VC-50 hi! Baby Sounder

V6CO. Limited Liability Co.

🏠 1185 Avenue of the Americas 3rd floor
New York NY 10036
United States
☎ 1-833-838-V6CO (8626)
✉ support@v6co.com
🌐 www.v6co.com

V6CO. reserves the right of product appearance, specifications and function modification and updating, without prior notification.
V6CO. Copyright 2021 V6CO. Limited Liability Company. All rights reserved.

VC-50

Hi! Baby Sounder



Fetal heart sound



Color display screen



Patterned Probe Design



Low-power



Digits/Curve display



Auto shutdown



VC-50 Pocket Fetal Doppler adopts Doppler technology in designing, it is a hand-held fetal heart rate detection device. Measured FHR value and waveform are displayed on the TFT screen. With easy and convenient operation, it can be used in hospital, clinic for daily self-check by pregnant woman, realizing early monitoring and care for life.

Function

- ◆ Beautiful appearance, easy to operate
- ◆ Patterned probe design, compact design, convenient to use
- ◆ High resolution screen
- ◆ Digits/Curve display
- ◆ Battery level indication
- ◆ Auto shutdown after no signal inputting for 60s
- ◆ High sensitive Doppler probe, fetal heart sound can be heard clearly for pregnancy more than 12 weeks
- ◆ Two sound output modes: built-in speaker and external headphone

Physical characteristic

- ◆ Dimension: 141.6mm(L) × 113.3 mm(W) × 25.4 mm(H)
- ◆ Weight: about 198 g(with batteries)

Performance

- ◆ Safety classification: internally powered equipment, type CF applied part
- ◆ Display: 1.77 " TFT screen
- ◆ FHR measurement and display range: 50 BPM ~ 240 BPM (BPM: beats per minute)
- ◆ Resolution: 1 BPM
- ◆ Accuracy: ± 2 BPM
- ◆ Rated working voltage: DC3 V
- ◆ Battery type: two 1.5V batteries (AA LR6)

Probe

- ◆ Nominal Frequency: 3.0 MHz
- ◆ Working Frequency: 3.0 MHz $\pm 10\%$
- ◆ Negative Peak Sound Pressure: $p_- < 1$ MPa
- ◆ Output Beam Intensity: $I_{ob} < 20$ mW/cm²
- ◆ Spatial-peak Temporal-average Derived Intensity: $I_{spta} < 100$ mW/cm²
- ◆ Ultrasonic Output Power: $P < 20$ mW
- ◆ Working Mode: Continuous wave Doppler
- ◆ Effective Radiating Area of Transducer: ≤ 208 mm²